

Anker SOLIX X1

Hybrid Single-Phase Energy Storage System

Power Module



Model	X1-H3.68K-S	X1-H4.6K-S	X1-H5K-S	X1-H6K-S
Battery Input				
Battery Type	LFP			
Charge Voltage Range	390 - 550 VDC			
Discharge Voltage Range	370 - 500 VDC			
Battery Capacity	5 - 30 kWh			
PV Input				
Max Input Power	7.36 kW	9.2 kW	10 kW	12 kW
Max Input Voltage	600 VDC			
MPPT Voltage Range	80 - 550 VDC			
Start-Up Voltage	100 VDC			
Rated Input Voltage	360 VDC			
Max PV Input Current	16 / 16 ADC			
1sc PV Array Short Circuit Current	20 / 20 A			
Number Of MPPTs	2			
Number Of Strings per MPPT	1			
AC Output (On-Grid)				
Rated Output Power	3.68 kW	4.6 kW	5 kW	6 kW
Max Output Apparent Power	4 kVA	5 kVA	5.5 kVA	6.6 kVA
Rated Output Voltage	220/230/240 V			
Rated Frequency	50/60 Hz			
Power Factor	0.8 ind - 0.8 cap			
THDI (@Rated Power)	< 3%			
AC Output (Off-Grid)				
Rated Output Power	3.68 kW	4.6 kW	5 kW	6 kW
Max Output Apparent Power	4 kVA	5 kVA	5.5 kVA	6.6 kVA
Peak Output Apparent Power (Duration)	7.2 kVA (10s)	10 kVA (10s)	10 kVA (10s)	10 kVA (10s)
Max Units In Parallel	3			
Rated Output Voltage	220/230/240 V			
Rated Frequency	50/60 Hz			
THDU (@Linear Load)	< 2%			
Switch Time	< 10 ms			
AC Input				
Max Input Apparent Power	7.2 kVA	10 kVA	10 kVA	10 kVA
Protection				
Anti-Isolation Protection	Yes			
Over Current Protection	Yes			
AC Short-Circuit Protection	Yes			
Over Voltage Protection	Yes			
DC Surge Prevention	Type II			
AC Surge Prevention	Type II			
Over Temperature Protection	Yes			
PV Input Reverse Polarity Protection	Yes			
Battery Input Reverse Polarity Protection	Yes			
Insulation Impedance Detection	Yes			
Residual Current Detection	Yes			
Efficiency				
Max Efficiency	97.4%	97.5%	97.4%	97.6%
European Efficiency	96.5%	96.7%	96.7%	97.1%

Connectivity	
Internet Connectivity	Wi-Fi, Bluetooth, Ethernet, 4G (Optional)
Interface	DI/DO, DRM
Other	
Weight	19 kg
W × H × D Dimensions (mm)	670 × 335 × 150
Noise	≤ 30dB*
Mounting Options	Ground or Wall**
Operation Temperature	-25 ° C to 60 ° C***
Relative Humidity	0 to 100%
Max Operating Altitude	Up to 4,000 m, Power Derates from 2,000 m
Ingress Protection Rating	IP66
Warranty	10 Years Limited****
Compliance Information (More information available upon request)	
Grid Connection Certifications	VDE-AR-N 4105, DIN VDE V 0124-100 (VDE V 0124-100), CEI 0-21, G99/1-9, G99/NI, C10/C11, NTS 2021 V2.1, UNE 2170021, UNE 217002, RD 647, AS/NZS 4777.2, EN 50549-1, EN50549-10, Order no. 208, DTIS-230206-BRL
Safety	EN IEC 62109-1, EN IEC 62109-2, AS 60947.3
EMC	EN IEC 61000-6-1, EN IEC 61000-6-3

*Tested in Anker laboratory at 1 m distance and typical voltage.

**Access rack required for wall mounting.

***Power derates once ambient temperature exceeds 45 °C.

****Refer to Anker SOLIX X1 Home Energy Storage System (Warranty Policy) for details.

Made in China.

Anker Innovations Limited